

**DECLARATION OF PERFORMANCE**

**Nr. BFCT-02-011**



Name or registered trade mark and contact address of the manufacturer/distributor:  
Coeck NV - De Laetstraat 6 - 2845 Niel - Belgium

Year: 13  
Harmonised technical specification: EN 14411:2012  
System 4

**Product:**

**Fuori** Luce, Scuro, Ombre 60x60x2

**Fuori Strutturato** Luce, Scuro, Ombre, Nero 60x60x2

**Dentro** Luce, Scuro, Ombre 60x60x1

Unique identification code of the product type: Dry-pressed ceramic tiles, with water absorption  $E_b \leq 0,5\%$ .

Intended uses: For internal and external walls and floorings.

Reaction to fire	A1FL/A1
Release of dangerous substance (only for GL ceramic tiles) - Cadmium - Lead	NPD
Breaking strength (thickness $\geq 7,5$ )	$\geq 1300$ N
Breaking strength (thickness $< 7,5$ )	$\geq 700$ N
Slipperiness DIN 51130	Fuori Luce, Scuro, Ombre: R10 Fuori Strutturato Luce, Scuro, Ombre, Nero: R11 Dentro Luce, Scuro, Ombre: R9
Tactility	NPD
Bond strength/adhesion	NPD
Thermal shock resistance	Pass
Durability for: - Internal use - External use: freeze-thaw resistance	Pass

The performance of the product identified is in conformity with the declared performances.  
This declaration of performance is issued under the sole responsibility of the manufacturer.  
Edited in Niel, 7 April 2014.

Ludo Coeck  
Managing Director